

(P21)HS035.025 PLP R SFYP

HS035 HEAT SEAL//25 White Lined Pulp

- Designed as a two-piece, pulp backed, induction heat seal and liner with an ethylene vinyl acetate based sealant layer that gives a tamper evident bond to Polyethylene (PE), Polypropylene (PP), Polyester (PET), Polystyrene (PS), Vinyl (PVC) and glass containers.
- Available with standard or custom print.

Typical Product Attributes

Construction

		SI (µm)	US (Mils)
Pulp		635,0	25.0
Wax		25,4	1.0
Paper		71,1	2.8
Aluminum Foil		8,9	0.35
Heat Seal		63,5	2.25
Minimum Width		25,4 mm	1.0 inch
Width Tolerance		± 1,6 mm	± 1/16

Properties

Water Vapor Transmission (WVTR)	Essentially Zero
Gas (O ₂) (GTR)	Essentially Zero

Regulatory Compliance

FDA Compliance	21 CFR 178.3710 Petroleum wax. 21 CFR 177.1350 Ethylene-vinyl acetate copolymers. 21 CFR 177.1210 Closures with sealing gaskets for food containers 21 CFR 176.180 Components of paper and paperboard in contact with dry foods. 21 CFR 176.170 Components of paper and paperboard in contact with aqueous and fatty foods.
Drug Master File (DMF)	2518
Other Compliances	USFDA Food Allergen Guidelines; California Proposition 65 Labeling Requirements; Limitations of Heavy Metals in Packaging per CONEG & EU 94/62/EC, Article 11

Original Date: 2016-03-25
 Revised Date: N/A
 Revision Number: 0
 Created by PEY

DISCLAIMER: This information is believed to be accurate at the time of printing and is subject to change without notice. Providing this information does not convey any licenses under any patent rights or intellectual property rights of Tri-Seal or others. TRI-SEAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON IT. Tri-Seal's only warranties for this product are those written warranties as may be agreed to by Tri-Seal and its customers. TRI-SEAL SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE.

Tri-Seal
 a Tekni-Plex company
 16125 Armour St. N.E.
 Alliance, OH 44601
 Tel: 330-821-1166 – Fax: 330-821-0364
 www.tri-seal.tekni-plex.com