

FoilSealTM **Technical Data Sheet**

.020" PS Foam FS 5-8

Revision: FS58-08192011

Product	.020" PS Foam FS 5-8			
Scope	One piece foam backed heat induction foil inner seal which will provide a tamper-evident bond to PE, PS, PET, PVC, PP and treated glass containers. It is recommended for liquid products and is an alternative to FS 5-4.			
Composition	Material	Standard	Metric	gamman gamman
	Backing Paper Foil Heat Seal	.020" .002" .0003" .0015"	.508 mm .0508 mm .0076 mm .0381 mm	Backing Paper Foil Heat Seal Inposition does not include adhesive, resin or wax bonding layers (if any).
FDA Status: 21 CFR 177.1210		Recommended Storage and Handling: Refer to Website.		
Drug Master File (DFM): #4544		EU / EP Reg.: Does not meet Article 3a of Reg. No. 2023/2006 and Article 3 of Reg. No. 1935/2004		
GTR Oxygen: Essentially Zero		MVTR: Essentially Zero		
Sealing to glass contaglass (treated or untreat that may or may not imp	eu) container.	vve suddest vou contact	formance or sea t your glass supp	Il integrity of this materials when applied to any plier for recommendations on glass treatments
Print Location (if any):	1			

Selig materials are compliant with current USFDA Food allergen Guidelines.

Selig materials are compliant with California Proposition 65 labeling requirements.

Selig materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

Recommended for use with dry food products. Is not suitable for use with fatty or alcoholic food types per ECC Reg. № 10/2011. Determining specific organoleptic compatibility per Article 3a of ECC Reg. № 2023/2006 is the responsibility of the food packager.

MSDS's are not required as Selig is not a chemical manufacturer or distributor and our products are 'articles' intended for food packaging per 29 CFR 1910.1200 (HazCom).

The information contained within this product data bulletin is to be used as a general guide in determining which structures are offered for sealing to specific container materials. All of the information which we provide is reliable to the best of our knowledge, but the accuracy thereof is not guaranteed. We suggest that consumers determine suitability for their own application.

www.seligsealing.com

USA Manufacturing 342 E Wabash Ave. Forrest, IL 61741, USA Fax: +1 (815) 657-7584

North American Sales 184 Shuman Blvd., Suite 310 Naperville, IL 60563, USA Phone: +1 (815) 785-2100 Phone: +1 (630) 922-3158 Fax: +1 (630) 922-8469

European Sales and UK Manufacturing Canada Manufacturing 635-637 Ajax Avenue Slough Trading Estate Slough Berkshire SL1 4BH UK Phone: +44 (0) 1753 773 000

Fax: +44 (0) 1753 773 111

145 Edward Street Aurora, Ontario Canada, L4G 1W3 8172 Niederglatt Phone: +1 (905) 727-0114 Fax; +1 (905) 727-8544

Switzerland Manufacturing Bahnhofstrasse 13 Phone: +41 (0) 44 851 50 50 Fax: +41 (0) 44 851 50 51