




TRIPLE DOT CORP.

Plastic Container Manufacturing

3302 S. Susan St. Santa Ana, CA 92704 Tel: (714) 241-0888 Fax: (714) 241-9888



T range:	88.29 – 89.18 mm
Max. label area:	40 x 288 mm
Min. wall thickness:	.5 mm
Material:	High Density Polyethylene



TRIPLE DOT CORPORATION

3302 S. Susan Street, Santa Ana, CA 92704
Tel: (714) 241-0888 Fax: (714) 241-9888

Scale: 1:1

Unit: mm

12-oz



HIGH DENSITY POLYETHYLENE

BAPOLENE[®] 2035 BLOW MOLDING

Description: Bapolene[®] 2035 is a high density polyethylene copolymer resin. Product offers a balanced combination of superior top-load strength and ESCR properties. It complies with FDA 21CFR 177.1520¹.

Application: General purpose blow molding, household chemical and cosmetic containers.

Values reported are typical and should not be interpreted as specification.

All data are based on compression-molded plaques.

Resin	Nominal Value	ASTM
Melt Index ² g/10 min.	0.35	D-1238
Density, g/cm ³	0.955	D-4883

GENERAL PROPERTIES		Nominal Value	ASTM
Tensile Strength @ Yld	psi	4,000	D-638
	MPa	28	
Flexural Modulus Tangent	psi	185,000	D-638
	MPa	1,276	
Elongation @ Brk	%	> 500	D-638
ESCR F50, 100% IGEPAL, Condition B	h	25	D-1693

¹ End use and/or migration limitations may apply.

² 190°C / 2,160g

THIS PRODUCT DATA SHEET EFFECTIVE AUGUST 2016 SUPERSEDES ALL DATA PREVIOUSLY PUBLISHED

BAMBERGER POLYMERS

Two Jericho Plaza, Jericho, New York, 11753, U.S.A. / Tel: 516-622-3600 / Fax: 516-622-3620 / Email: bpinfo@bapoly.com

Bamberger Polymers does not guarantee the applicability or the accuracy of the information contained herein, nor the suitability of the products described herein for any particular purpose. No warranties of any kind, either express or implied, are made with respect to the products described herein or with respect to the use of the products described herein. The user assumes all risk and liabilities in connection with such usage.



Bamberger Polymers

SAFETY DATA SHEET

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

SECTION 1

IDENTIFICATION

Product Name: Polyethylene (High Density Polyethylene)

Covers the following grade(s): **Bapolene 2035**

Product Type: Pellet/Flake

Use: Manufacture of various plastics articles.

Supplier:

Bamberger Polymers, Inc.

Two Jericho Plaza, Suite 109

Jericho, NY 11753

Business Phone: (800) 888-8959

SECTION 2

HAZARDS IDENTIFICATION

OSHA Classification of the substance or mixture (GHS-US):

- Combustible Dust

Label Elements

- Signal word (GHS-US): Warning
- Hazard Statement(s): If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Acute Toxicity

No additional information available.

Additional Information

Keep container tightly closed and away from heat, hot surfaces, sparks, open flames and other ignition sources. Processing the polymer at high temperatures may form vapors that irritate the eyes and respiratory tract.

No smoking. Prevent dust accumulation. Airborne clouds of fine dust may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Spilled pellets may create a slipping hazard. Sweep up spillage and dispose of properly.

SECTION 3**COMPOSITION / INFORMATION ON INGREDIENTS**

Substance: NA

Mixture:

Ingredient Name	CAS #	% Wt.
Ethylene-1-butene	25087-34-7	≤ 100
Ethylene-1-hexene-1	25213-02-9	≤ 100
Ethylene-1-octene	26221-73-8	≤ 100
Polyethylene Homopolymer	9002-88-4	≤ 100
Additives	Proprietary/Trade Secret	NA

** Compositions are typical values not part of any specification(s).*

To the best of our knowledge, there are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and require reporting in this section.

SECTION 4**FIRST AID MEASURES****Description of First Aid Measures****Eye Contact**

Flush eyes with clean, cold, low-pressure running water for at least 15 minutes. Seek immediate medical attention.

Skin Contact

If molten material contacts skin, immediately flush skin with large amounts of cold water. No attempt should be made to peel polymer from the skin or to remove clothing attached with molten material. Thermal burns require immediate medical attention.

Inhalation

Remove victim to well-ventilated area. If not breathing, provide artificial respiration by trained personnel. If difficulty breathing, provide give oxygen and seek medical attention.

Ingestion

If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Handling and/or processing of this material may generate dust which may cause mechanical irritation of the eyes, skin, nose and throat. High dust concentrations have a potential for combustion or explosion.

Most Important Symptoms/Effects, Acute and Delayed**Skin**

No significant irritation expected. Heated material can cause serious thermal burns. At high process temperatures, fumes may cause irritation of the nose and throat.

Eyes

Possible mechanical irritation may manifest itself as local redness with possible discomfort. Heated material can cause thermal burns. When heated, vapors formed may irritate eyes. Material is dusty and may scratch surface of eye.

Inhalation

Exposure to high concentration of airborne particles may cause upper respiratory tract irritation. If heated, the product may form fumes which could cause irritation of the respiratory tract, coughing, nausea, and shortness of breath.

Ingestion

May cause choking, diarrhea, nausea, or discomfort in the abdominal region.

Indication of any immediate medical attention and special treatment

No additional information is available.

SECTION 5**FIRE FIGHTING MEASURES****Suitable Extinguishing Media**

High dust concentrations have potential for combustion or explosion. In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable Extinguishing Media

Do *not* use water jet/stream.

Specific Hazards Arising from the Chemical

Fire- May be combustible at high temperature.

Explosion Hazards

Material is not explosive as defined by established regulatory criteria. May ignite if ignition source is available. Potential dust explosion hazard.

Hazardous Thermal Decomposition Products

Flammability

Products of Combustion

Combustion can produce carbon dioxide (CO₂), carbon monoxide (CO), hydrocarbons, aldehydes, organic vapors and other harmful products. Possible black smoke and soot.

Firefighting Protection

Wear NIOSH-approved positive pressure, self-contained breathing apparatus (SCBA) and full protective gear. Engage fire from a protected location. Avoid raising powdered materials into airborne dust, creating an explosion hazard. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Prevent fire-fighting water from entering environment

May re-ignite after fire has been extinguished.

SECTION 6

ACCIDENTAL RELEASES MEASURES

Personal Precautions, Protective Equipment and Emergency procedures

Eliminate all ignition sources and contain spill. Granules spilled on the floor can cause slipping. Fine dust clouds may form explosive mixtures with air. Do not touch or walk through spilled material. Use suitable protective equipment.

Environmental and Clean-Up Methods

If emergency personnel are unavailable, vacuum or carefully collect spilled material(s), and place in an appropriate container for disposal. Recovered material should be packaged, labeled, transported, and disposed of in conformance to consistent with all applicable laws and regulations. If heated material is spilled, allow to cool before proceeding with cleanup methods. Avoid creating dusty conditions and prevent wind dispersal. Avoid contact of spilled material with soil and prevent runoff from entering sewers and waterways.

Personal Protection

Personnel should wear proper safety equipment.

SECTION 7

HANDLING AND STORAGE

Handling

Do not smoke, drink or eat when storing, handling or using this product. Always wash hands after handling the product.

Keep away from open flame or sources of ignition. There is a risk of being splashed with molten materials. At high temperatures, potentially toxic/irritating fumes may result from heated material - do not inhale fumes or vapor from molten product. Use with adequate ventilation. When handling hot material, wear protective gloves, clothing and face shield that are able to withstand the temperature of the molten product. After handling, always wash hands thoroughly with soap and water. Pneumatic conveying and other mechanical handling can generate combustible dust and static electrical charges. Earth all equipment.

High dust concentrations have a potential for combustion or explosion. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Electrostatic charges may be generated when emptying sacks. It is recommended that sacks are emptied away from explosive environments.

Storage

Keep container dry, tightly closed, and stored in a well-ventilated area. Avoid contact or proximity to strong oxidizing agents. Pallet stock slippage and forklift truck maneuvers can cause injury. It is recommended that adequate procedures covering storage handling of pallets are implemented and based on good manufacturing practices.

Store at room temperature and protect from heat and direct sunlight. Store in a dry, cool, well-ventilated area. Containers that have been opened must be properly resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate procedures to avoid environmental contamination

Incompatible materials: strong oxidizing agents.

SECTION 8**EXPOSURE CONTROLS/PERSONAL PROTECTION**

Occupational Exposure Limits

Ingredients	Type	Limit Value	Basis
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust	TWA	10 mg/m ³ (Inhalable)	US (ACGIH) 2005
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust	TWA	3 mg/m ³ (Respirable)	US (ACGIH) 2005
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust	TWA	15 mg/m ³ (Total Dust)	US (OSHA) 2005
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust	TWA	5 mg/m ³ (Respirable)	US (OSHA) 2005

Control Measures

Use enclosures around process, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If high concentrations of airborne matter or fumes are generated, use ventilation to ensure levels are kept below the exposure limit. Clothing and shoes should be dusted before re-used.

Personal protection**Eyes**

Safety glasses with side shields are required as minimum requirements. Use full-face respirator if a high dust concentration is generated.

Skin

Minimize contact. The use of heat-resistant protective gloves and clothing and face shield is good industrial practice and recommended.

Respiratory

Product processing may produce dust, vapor or fumes. To minimize risk of overexposure to dust, vapor or fumes it is recommended to use process enclosures and a local exhaust system, and that the working area is properly ventilated. If ventilation is inadequate, use certified respirator that will protect against dust/mist. Do not consume food in the work area.

Hands

Use of heat-resistant protective gloves, clothing and face shield capable of withstanding temperature of molten product, is good industrial practice. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves. Since even the best chemically resistant glove will break down after repeated chemical exposures, gloves should therefore be chosen in consultation with the supplier/manufacture and with a full assessment of the working conditions.

Consult your local authorities, supervisor or standard operating procedures for special handling directions and acceptable exposure limits.

SECTION 9**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	
Physical state/form	Solid (pellets or powder)
Color	Opaque / Translucent / White
Odor	Mild to none
Safety Data	
Lower explosion limit	No data available
Upper explosion limit	No data available
Flammability (solid, gas)	Polymer will burn but does not easily ignite.
Oxidizing properties	Not considered an oxidizing agent.
Autoignition temperature	> 572 °F (300 °C)
Decomposition temperature	Not determined
pH	No data available
Approximate melting point range	122 - 338 °F (50 - 170 °C)
Boiling point/boiling range	No data available
Flash point	No data available
Vapor pressure	Not applicable
Density	< 1 g/cm ³
Water solubility	Negligible
Partition coefficient: n-octanol/water	No data available
Viscosity	No data available
Relative vapor density	No data available
Evaporation rate	No data available

SECTION 10**STABILITY AND REACTIVITY****Reactivity**

No known reactivity hazards.

Chemical Stability

Stable under appropriate handling and storage conditions.

Conditions to avoid

Excessive temperatures, strong oxidizers, and all possible sources of ignition (spark or flame), heat, and direct sunlight. Avoid dust formation.

Incompatibility

Strong oxidizing materials, fluorine, halogens, benzene, aromatic and chlorinated hydrocarbons, nitric and perchloric acids and others.

Decomposition products *(not expected to decompose under normal conditions)*

Combustion can produce carbon monoxide and/or carbon dioxide and other toxic products (fumes). Decomposition can yield traces amount of hydrocarbons. Degradation products may include, among others, aldehydes, alcohols, ketones, and organic acids.

Hazardous polymerization is not expected to occur.

SECTION 11

TOXOLOGICAL INFORMATION

Likely Routes of Exposure: oral, dermal, inhalation, ingestion.

Acute toxicity: Not classified.

Acute Toxicity (Listed for components where information is available)			
PE	LD ₅₀ oral rat	> 8000 mg/kg	Based on polyethylene homopolymer
Polyethylene (25213-02-9 or 25087-34-7 or 9002-88-4)	LD ₅₀ oral rat	> 8000 mg/kg	Based on polyethylene homopolymer

- Skin corrosion/irritation: Not classified
- Acute oral toxicity: Not classified
- Acute inhalation toxicity: Not classified
- Acute dermal toxicity: Not classified
- Serious eye damage/irritation: Not classified. Mechanical irritation is possible.
- Respiratory or skin sensitization: Not classified
- Carcinogenicity: IARC Group 3 - Not classifiable
- Germ cell mutagenicity: Not classified
- Reproductive toxicity: Not classified
- Specific target organ toxicity (single exposure): Not classified
- Specific target organ toxicity (repeated exposure): Not classified
- Aspiration hazard: Not classified

This product is not considered a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard.

Other Information

During thermal processing polyolefins can release vapors and gases (aldehydes, ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and limited epidemiological evidence.

SECTION 12

ECOLOGICAL INFORMATION

Ecotoxicology Assessment

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Wildlife may ingest plastic pellets or bags. Although not toxic, such materials may physically obstruct the digestive system, causing starvation or death.

No testing has been performed by the manufacturer(s).

Acute aquatic toxicity: Not classified

Chronic aquatic toxicity: Not classified

Persistence and degradability

Biodegradability: Not inherently biodegradable.

Bioaccumulative potential: This material is not expected to bioaccumulate.

Mobility

This product is expected to float on water, and is not likely to move rapidly with surface or groundwater flows due to its low water solubility. This material is insoluble in water.

Results of PBT and vPvB assessment: Not applicable.

Other Information

This material is not volatile and insoluble in water. Avoid release to the environment.

SECTION 13

DISPOSAL CONSIDERATIONS

The information in this SDS pertains only to the product as shipped.

Waste Information

Avoid contact of spilled material and/or runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, and treatment, storage or disposal facilities. Dispose of in accordance with all applicable Federal, State and local control regulations. Recycle the material to fullest extent possible.

Consult your local, regional and federal (EPA) authorities for all pertinent regulations and procedures.

SECTION 14

TRANSPORT INFORMATION

Polyethylene, other than liquid, is not regulated.

Regulatory Authority	Shipping Description
DOT (USA)	Not regulated as a hazardous material or dangerous goods for transportation.
IATA	Not regulated as a hazardous material or dangerous goods for transportation.
IMDG	Not regulated as a hazardous material or dangerous goods for transportation.

This information is not intended to convey all specific regulatory or operational requirements/ information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15

REGULATORY INFORMATION

TSCA

All components of this product are listed or exempted from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

SARA 311/312 Hazard Classification

Fire

SECTION 16

OTHER INFORMATION

Label requirements


This product has been evaluated and does not require any hazard warning on the label under established regulatory criteria.

HMIS

Health Hazard: 0

Flammability: 1

Physical hazards: 0




NFPA

Health: 0

Fire Hazard: 1

Reactivity: 0



Rating Scale Information

HMIS: (0 = minimal hazard; 4 = severe hazard)

NFPA: (0 = minimal hazard; 4 = severe hazard)

NOTICE

This Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bamberger Polymers.

Bamberger Polymers does not assume any liability whatsoever for the accuracy or completeness of the information, the use of the information, or the use of the product mentioned herein. Final determination of the suitability of any information or product contemplated, the manner of use, environmental protection, and the health and safety of its employees is the sole responsibility of the user. Bamberger Polymers shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product. Although certain hazards may be described herein, we cannot guarantee that these are the only hazards which exist. All materials may present unknown hazards and should be used with caution. Except as stated in this document, no representations are made as to the physical properties or quality of this product.

Nothing herein waives or modifies any of the Seller's terms and conditions of sale as it pertains to this product.

PRODUCT INFORMATION

Colortech F100320 (or 51219-18) White

Colortech F100320 (or 51219-18) White is a premium quality concentrate suitable for a broad range of applications including blown and cast film, sheet, pipe and profile extrusion, injection molding and blow molding. It has been designed to provide color and opacity equivalent to a standard 50% titanium dioxide concentrate when used at identical addition levels. This product is an economical alternative to a standard 50% TiO₂ concentrate.

The carrier resin used in the formulation of Colortech F100320 (or 51219-18) is a high flow linear low density polyethylene.

Nominal Pellet Size	-	42.0 pellets/g
Nominal Bulk Density	-	80.1 lbs/ft ³
Specific Gravity	-	2.25
Max. Recommended Operating Temp.	-	260°C/ 500°F

All components used in the manufacture of Colortech F100320 (or 51219-18) White conform to specifications contained in U.S.A. Food and Drug Administration (FDA) 21 CFR and may be used in the United States as components of articles intended for use in food contact applications, subject to any limitations outlined in the regulations. Contact Colortech Regulatory Affairs (regulatoryrequest@colortech.com) to request specific details regarding product limitations and conditions of use.

This product does not contain diarylide or pyrazolone pigments and is considered to be heavy metal free. Trace heavy metal levels comply with current CONEG guidelines (total lead, mercury, cadmium, and hexavalent chromium concentration less than 100 ppm).

IMPORTANT – The following supersedes buyer's documents. The information provided is based on Colortech test data or knowledge which is, to the best of our ability, believed to be a true & accurate representation of the product. ***This data shall, in no event, be held to constitute or imply any warranty, guarantee of performance, express or implied commitment of merchantability or fitness of use for a particular purpose, by Colortech.*** Our formal specifications define the limit of Colortech's commitment. Because use conditions and applicable laws may differ by location and may change with time, customer is responsible for determining whether products and the information herein are appropriate for customer's use. Furthermore, no liability whatsoever will be accepted by Colortech with regard to the customer's workplace handling, processing, product use or application, and disposal practices which in all cases must be conducted in compliance with applicable laws and other governmental enactments.

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: This product has not been tested for, and is therefore not recommended for (a) any application for which there will be contact with human mucous membranes, abraded skin or tissue, or internal body fluids or tissues, for any length of time, (b) any uses where implantation within the human body is intended, and (c) any application involving female pregnancy or specifically intended to promote or interfere with human reproduction.

Rev1. 03/21
WA
110LM5759

